



ALTA® Wireless Accelerometer - G-Force Max-Avg Sensor

General Description

[ALTA® Wireless Accelerometer - G-Force Max-Avg Sensors](#) measure the maximum and average g-force levels that occur on the X, Y, and Z axes over a user-defined report interval.

Key Features

- ▶ Measures on three axes
- ▶ Resolution: 0.001 g
- ▶ Accuracy: $\pm 2.5\%$ on all axes
- ▶ Range: 2 g, 4 g, or 8 g
- ▶ High Pass Filter (HPF) optional to remove static forces
- ▶ Configurable thresholds for critical condition monitoring

Principles of Operation

The ALTA Wireless Accelerometer - G-Force Max-Avg Sensor uses a MEMS (microelectromechanical system) accelerometer to measure and record acceleration over a user-configurable time interval or Heartbeat. On every Heartbeat, the data collected is analyzed, and Max and Average results are forwarded to the gateway, making the data available in iMonnit or another approved data service.

Example Applications

- ▶ Unauthorized access via a fence breach
- ▶ Physical barrier integrity
- ▶ Abnormal motor shake
- ▶ Wind turbine abnormalities
- ▶ Assembly line irregularities
- ▶ [Additional applications](#)


Features of Monnit ALTA Sensors

- Wireless range of 2,000+ feet through 18+ walls¹
- Frequency-Hopping Spread Spectrum (FHSS)
- Best-in-class interference immunity
- Best-in-class power management for longer battery life²
- Encrypt-RF® Security (Diffie-Hellman Key Exchange + Advanced Encryption Standard (AES)-128 Cipher Block Chaining (CBC) for sensor data messages)
- Sensor logs 2000 to 4000 readings if the gateway connection is lost (non-volatile flash, persists through power cycling):
 - 10-minute Heartbeats = ~ 22 days
 - 2-hour Heartbeats = ~ 266 days
- Automatic over-the-air updates to sensor firmware (future-proof)
- Free iMonnit Basic Online Wireless Sensor Monitoring and Notification System to configure sensors, view data, and send alerts via SMS text, email, and voice call





¹ Actual range may vary depending on the environment and gateway

² Battery life is determined by the sensor reporting frequency and other variables. Other power options are also available.

Wireless Range Comparison




Technical Specification | ALTA® Wireless G-Force Max-Avg Sensors

G-Force	Range options	2g, 4g, 8g
	Sensitivity	4096 count/g @ 2 G, 2048 count/g @ 4 G, 1024 count/g @ 8 G
	Measurement accuracy	±2.5 % on all axes
	Accelerometer measurement rate	6 Hz, 12 Hz, 50 Hz, 100 Hz ¹
	High Pass Filter (HPF) cutoff	4 Hz
	Resolution	0.001 g
ALTA Wireless	Data logging	Sensor logs 2000 to 4000 readings if gateway connection is lost (non-volatile flash, persists through power cycling): 10-minute Heartbeats = ~22 days - 2-hour Heartbeats = ~266 days
	Wireless protocol	ALTA Proprietary Frequency-Hopping Spread Spectrum (FHSS)
	Wireless transmission power (EIRP)	50 mW (900MHz), 25 mW (868 MHz), 10 mW (433 MHz)
	Wireless range	2,000+ ft. through 18+ walls with the ALTA XL® Gateway
	Security	Encrypt-RF® (256-bit key exchange and AES-128 CTR)
General	Battery voltage range	2.0 to 3.8 VDC
	Operating altitude (non-pressurized environments)	-15.2 to 1,982 m (-50 to 6,500 ft) ¹
	Storage altitude (non-pressurized environments)	-15.2 to 3,048 m (-50 to 10,000 ft) ¹
	Operating humidity	5 to 85% RH (non-condensing)
	Certifications	900 MHz sensors: FCC ID: ZTL-G2SC1 and IC: 9794A-G2SC1 . 868 and 433 MHz sensors tested and comply with: EN 55032: 2015/A11:2020 ; EN 55035:2017/A11:2020 ; ETSI EN 300 220 V3.2.1 (2018-06) ; ETSI EN 301 489-3 V2.2.0. (2021-11) ; and ETSI EN 303 645 . All sensors tested and comply with: EN 61010-1 and EN 60950 and meet RoHS 2015/863 and REACH 224 (June 2022) , according to IEC 63000:2016/AMD1:2022 .
	   	

1. Operating and storage altitude without DC power supply is -30.48 to 9144 m (-100 to 30000 ft).




This sensor reports the following eight values:

- X-Max: Maximum g-force on X-axis measured over Heartbeat
- Y-Max: Maximum g-force on Y-axis measured over Heartbeat
- Z-Max: Maximum g-force on Z-axis measured over Heartbeat
- M-Max: Maximum g-force magnitude measured over Heartbeat
- X-Avg: Average g-force on X-axis measured over Heartbeat
- Y-Avg: Average g-force on Y-axis measured over Heartbeat
- Z-Avg: Average g-force on Z-axis measured over Heartbeat
- M-Avg: Average g-force magnitude measured over Heartbeat




Monnit Wireless Accelerometer Orientation (Industrial)

Gravity



Technical Specifications ALTA® Enterprise	
Battery ¹	2x 1.5V AA Alkaline, 1500 mAh, (standard) 2x 1.5V AA Lithium, 3000 mAh, (optional)
Battery Life ²	6 Hz: ~ 4 year lifetime at 10+ minute Heartbeat. 12 Hz: ~ 4 year lifetime at 10+ minute Heartbeat. 50 Hz: ~ 2 year lifetime at 10+ minute Heartbeat. 100 Hz: ~ 1 year lifetime at 10+ minute Heartbeat.
External line-power option ³	Input voltage: 5.0-12.0 V Power jack: 2.1 x 5.5 mm barrel, center positive
Operating temperature range ⁴	-18°C to 55°C (0°F to 130°F) - AA Alkaline Batteries -25°C to 60°C (-13°F to 140°F) - AA Lithium L91 Batteries 0°C to 40°C (32°F to 104°F) - US 5V Power Supply 10°C to 40°C (50°F to 104°F) - International 5V Power Supply
Wireless antenna type	1/4-wave, 20 gauge wire whip, 3.5" (900/868MHz), 7"
Weight	3.7 oz. (105 g)

1. Hardware cannot withstand negative voltage. Please take care when inserting and removing batteries.
2. If the Heartbeat is above 10 minutes it only changes the battery life by a month or two.
3. Batteries will provide backup power in the case the external power is removed.
4. Operating below 0°C (32°F) degrees will reduce battery life.



Technical Specifications | ALTA® Industrial

Battery	1x 3.6V AA Lithium Thionyl Chloride, 1500mAh, pre-installed
Battery Life ¹	6 Hz: ~ 4 year lifetime at 10+ minute Heartbeat. 12 Hz: ~ 4 year lifetime at 10+ minute Heartbeat. 50 Hz: ~ 2 year lifetime at 10+ minute Heartbeat. 100 Hz: ~ 1 year lifetime at 10+ minute Heartbeat.
Operating temperature range ²	-40°C to 85°C (-40°F to 185°F)
Wireless antenna type	1/2-wave waterproof dipole with RP-SMA connector and swivel neck; dBi of 3.0 (900/868MHz) or 2.5 (433 MHz); length of 8.27" (210mm) (900/868MHz) or 7.68" (195mm) (433 MHz); diameter at thickest point of 0.55" (14mm)
Weight	4.7 oz. (133 g)
Enclosure rating	IP-65 (dust-proof and waterproof but not submersible) NEMA 1, 2, 4, 4x, 12, and 13 rated, sealed, and weatherproof UL Listed to UL508-4x specifications (File E194432)

1. If the Heartbeat is above 10 minutes, it only changes the battery life by a month or two.
2. Operating below 0°C (32°F) degrees will reduce battery life.

Commercial-Grade Sensors

Monnit commercial-grade sensors are designed for applications in ordinary environments (normal room temperature, humidity, and atmospheric pressure). Do not use these sensors under the following conditions, as these factors can deteriorate the product characteristics and cause failures and burnout.

- Corrosive gas or deoxidizing gas: chlorine gas, hydrogen sulfide gas, ammonia gas, sulfuric acid gas, nitric oxide gas, etc.
- Volatile or flammable gas
- Dusty conditions
- Low-pressure or high-pressure environments
- Wet or excessively humid locations
- Places with salt water, oils, chemical liquids, or organic solvents
- Where there are excessively strong vibrations
- Other places where similar hazardous conditions exist

Use these products within the specified temperature range. Higher temperatures may cause deterioration of the characteristics or the material quality.

Industrial-Grade Sensors | Type 1, 2, 4, 4X, 12, and 13 NEMA-Rated Enclosure

Monnit's industrial sensors are enclosed in reliable, weatherproof NEMA-rated enclosures. Our NEMA-rated enclosures are constructed for indoor and outdoor use and protect the sensor circuitry against the ingress of solid foreign objects like dust and the damaging effects of water.

- Safe from falling dirt
- Protects against wind-blown dust
- Protects against rain, sleet, snow, splashing water, and hose-directed water
- Increased level of corrosion resistance
- Will remain undamaged by ice formation on the enclosure



Monnit Corporation

3400 South West Temple • Salt Lake City, UT 84115 • 801-561-5555
www.monnit.com